

Product Specifications

imageRUNNER ADVANCE C2030
shown

Inner Finisher-C1
with Inner Finisher
Additional Tray-A1



Inner 2-Way Tray-F1



Utility Tray-A2



Copy Tray-J1

Cassette Feeding
Unit-AF1



Cabinet Type-D

Main Unit

System Type

Color Digital Multifunction Imaging System

Functions

Standard: Copy, Print (UFR II), Scan, Send

Optional: Print (PCL, Adobe® PostScript® 3™),
Fax (Up to 2 Lines)

Operation Panel

5.7" VGA Full Color TFT Screen

Memory

Standard: 2GB RAM

Maximum: 2GB RAM

Hard Disk Drive

Standard: 80GB

Maximum: 80GB

Network Interface Connection

Standard: 10/100Base-TX, 1000Base-TX

Optional: Wireless LAN (IEEE 802.1X)

Other Interface

Standard: USB 2.0 (Host)x2, USB 2.0 (Device)

Optional: Device Port (USB 2.0 (Host)x2),
Copy Control Interface

Copy/Print Output Speed (BW/Color)

Letter: **C2030:** Up to 30/30 ppm
C2020: Up to 20/20 ppm

Legal/Ledger: **C2030:** Up to 15 ppm
C2020: Up to 15 ppm

Paper Sources (20 lb. Bond)

Standard: 250-sheet Cassette, 550-sheet
Cassette, 100-sheet Stack Bypass

Optional: Dual 550-sheet Cassettes

Maximum: 2,000 Sheets

Output Paper Capacity (20 lb. Bond)

Standard: 250 Sheets (Inner Tray)

Maximum: 850 Sheets (w/Inner Finisher and
Copy Tray)

Output Paper Sizes

Cassette 1: 11" x 17", Legal, Letter, Letter-R,
Statement-R, Executive, Custom
Size [5-7/8" x 7-1/8" to 11-3/4" x
16-1/2" (148mm x 182mm to 297mm
x 420mm)]

Cassette 2-4: 12" x 18", 11" x 17", Legal, Letter,
Letter-R, Statement-R, Executive,
Custom Size [5-1/2" x 7-1/8" to 12" x
15-3/8" (140mm x 182mm to 304mm
x 457mm)]

Bypass: 12" x 18", 11" x 17", Legal, Letter,
Letter-R, Statement, Statement-R,
Executive, Custom Size [3-7/8" x
5-1/2" to 12-5/8" x 18" (99mm x
140mm to 320mm x 457mm)]

Other Options: Envelope Feeder Attachment**
(COM10 No.10, Monarch, DL, ISO-C5)

Acceptable Paper Weights

Cassette 1: 17 lb. Bond to 32 lb. Bond (64 to
120g/m²)

Cassette 2-4: 17 lb. Bond to 60 lb. Cover (64 to
163g/m²)

Bypass: 17 lb. Bond to 80 lb. Cover (64 to
220g/m²)

Duplexing

Paper Size: Standard Automatic Trayless
Duplexing (Executive to 12" x 18")

Paper Weights: 17 lb. Bond to 32 lb. Bond (64 to
120g/m²)

Special Media Support

Tracing, Labels, Transparency, and Envelopes

Warm-up Time

From Power On: 38 Seconds

From Sleep Mode: 10 Seconds

Power Requirements/Plug

120V AC, 60Hz, 7.5A/NEMA 5-15P

Power Consumption

Maximum: 1,500W

Sleep Mode: 1W

Dimensions (H x W x D)

36-1/2" x 22-1/4" x 26-3/4"
(928mm x 565mm x 680mm)

Installation Space (W x D)

33-1/4" x 26-3/4" (846mm x 680mm)
(When the Stack Bypass Tray is extended)

Weight

Approximately 209 lb. (95 kg)²

Toner (Estimated Toner Yield @5% Coverage)

Black: 23,000 Images

Color (C,M,Y): 19,000 Images

Image Reader Unit

Scan Resolution

Up to 600 x 600 dpi

Acceptable Originals

Sheet, Book, 3-Dimensional objects [up to 4.4 lb. (2kg)]

Maximum Original Size

Up to 11" x 17"

Document Feeder

Scan Method

Duplex Automatic Document Feeder

Acceptable Originals

Paper Sizes: 11" x 17", Legal, Letter, Letter-R,
Statement, or Statement-R

Paper Weights: 13 lb. Bond - 32 lb. Bond
(50 - 128g/m²)

Scan Speed (BW/Color; Letter)

Simplex: Up to 44/44 ipm (300 dpi)
Up to 30/30 ipm (600 dpi)

Duplex: Up to 19/19 ipm (300 dpi)
Up to 13/13 ipm (600 dpi)

Paper Capacity (20 lb. Bond)

50 Sheets



C2030 C2020

Main Unit (continued)

Copy Specifications

First-Copy-Out Time (Letter)

BW: 5.9 Seconds

Color: 8.9 Seconds

Multiple Copies

1-999

Color Mode

Auto Color, Full Color, Black, Single Color, Two Colors

Copy Exposure

Automatic or Manual (9 Levels)

Magnification

25% - 400% (1% Increments)

Preset Reductions

25%, 50%, 64%, 73%, 78%

Preset Enlargements

121%, 129%, 200%, 400%

Basic Copy Features

Preset R/E Ratios by Area, Finishing, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Sample Set, Setting Confirmation/Cancel, Standard Keys, Reset, Guide Display, Job Duration Display, Reserved Copying

Special Copy Features

Two-page Separation, Cover/Sheet Insertion, Transparency Interleaving, Shift, Margin, Frame Erase, Image Combination, Different Size Original, Job Build, Job Done Notice, Scan Image Check, Mode Memory, Recall, Negative/Positive Inversion, Image Repeat, Mirror Image, Sharpness, Secure Watermark, Page Numbering, Copy Set Numbering, Watermark and Date

Print Specifications

Processor

Canon Dual Custom Processor (Shared)

Memory

Standard: 2GB RAM

Maximum: 2GB RAM

Hard Disk Drive

Standard: 80GB

Maximum: 80GB

Maximum Engine Resolution1200 x 1200 dpi[†]**PDL Support**

Standard: UFR II

Optional: PCL 5c/6, Adobe® PostScript® 3™

Print Driver Supported OS

UFR II: Windows® (Windows 2000/XP/Windows Vista®/7/Server 2003/Server 2008/), Citrix MetaFrame, Macintosh® (OS X 10.2.8 or Later)

PCL 5c/6: Windows (Windows 2000/XP/Windows Vista®/7/Server 2003/Server 2008/Windows Vista), Citrix MetaFrame

PostScript 3: Windows (Windows 2000/XP/Windows Vista®/7/Server 2003/Server 2008/Windows Vista), Citrix MetaFrame, Macintosh (OS X 10.2.8 or Later)

XPS: Windows (Windows Vista®/7/Server 2003/Server 2008)

Direct Print SupportStandard: TIFF, JPEG, EPS^{††}Optional: PDF, XPS^{††}**Print Features**

Suspended Job Timeout, Subset Finishing (PS only), Profile Settings, Secured Print, Watermark, Page Border, Header/Footer, Page Layout, Two-sided Printing, Collating, Grouping, Mixed Paper Sizes/Orientations, Offsetting, Printing on Transparencies, Front/Back Covers, Black-and-white Printing, Objective, Color/Black-and-white Auto Detect, Toner Reduction, Poster Printing

Scan Specifications

Network TWAIN Scan

Standard

Network Scan Utility

Color Network ScanGear

Universal Send Specifications

Sending Method

E-Mail, I-Fax, File Server (FTP, SMB, WebDAV), Super G3 Fax (Optional)

Color Mode

Auto Color Select (Full Color/Grayscale) Auto Color Select (Full Color, BW) Full Color, Grayscale, BW

Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100

Address Book Capacity

Maximum 1,800 Destinations (Including 200 One-Touch Buttons)

Communication Protocol

File: FTP (TCP/IP), SMB (TCP/IP), WebDAV

E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)

File Format

Standard: TIFF, JPEG, PDF, PDF (Compact), PDF (Apply Policy), PDF (Optimized for Web), PDF/A-1b, XPS, XPS (Compact)

Optional: PDF (Trace & Smooth), PDF/XPS (OCR), PDF (Encrypted), PDF/XPS (Digital Signature), PDF (Reader Extensions)

I-Fax Data Format

BW: TIFF (MH, MR, MMR)

Fax Specifications

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 Kbps

G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution

400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi

Sending/Recording Size

Statement to 11" x 17"

Fax Features

Job Forwarding, Different-size Originals, Adjusting Overall Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Selecting the Telephone Line (when sending fax), Delayed Send, Preview, Finished Stamp, Job Done Notice, Original Type, Two-Sided Original, Book to Two pages

Store Specifications

Memory Media

Standard: USB Memory

Optional: SD, SDHC, CompactFlash, Memory Stick, Microdrive

Security Specifications

Standard

Department ID Management, Single Sign On-H, Access Management System (Device and Function Level log-in), Secured Print, Trusted Platform Module, IPV6, Restricting Features (Restricting the Send Function, Restricting New Addresses on Address Book), SSL Encrypted Communication, SNMPv1/v3, MAC/IP Address Filtering, SMTP Authentication, POP Authentication before SMTP, HDD Format, Adobe® LiveCycle® Rights Management ES2 Integration

Optional

Removable HDD, HDD Erase, HDD Encryption, Encrypted Secure Print, Encrypted PDF, Document Scan Lock,^{†††} IPsec, Secure Watermark

Environmental Information

- ENERGY STAR® Qualified
- Blue Angel
- RoHS Compliant
- WEEE Directive
- Ecomark



Optional Accessories

Paper Supply Options

Cassette Feeding Unit-AF1

Paper Capacity:	550 Sheets x 2 Cassettes (20 lb. Bond)
Acceptable Paper Weight:	17 lb. Bond to 60 lb. Cover (64 to 163g/m ²)
Acceptable Paper Size:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement-R, Executive, Custom Size [5-1/2" x 7-1/8" to 12" x 15-3/8" (140mm x 182mm x 304mm x 457mm)]
Power Source/Maximum Power Consumption:	From the Main Unit/Approximately 30W
Dimensions (H x W x D):	9-3/4" x 22-1/4" x 25-5/8" (248mm x 565mm x 650mm)
Weight:	Approximately 61 lb. (27.5kg)

Envelope Feeder Attachment-D1□□

Paper Capacity:	50 Sheets (or 30mm in height)
Acceptable Envelope Sizes:	COM10 No.10, Monarch, DL, ISO-C5
Feeding Speed:	10 ppm
Dimensions (H x W x D):	3-1/4" x 17-1/4" x 12-1/8" (81mm x 439mm x 307mm)
Weight:	Approximately 2.6 lb. (1.2kg)

Output Options

Copy Tray-J1

Total Output Capacity:	100 Sheets (20 lb. Bond)
Acceptable Paper Weight:	17 lb. Bond to 32 lb. Bond (64 to 120g/m ²)
Acceptable Paper Size:	11" x 17", Legal, Letter, Letter-R, Statement-R, and Executive
Dimensions (H x D x W):	5-5/8" x 14-3/8" x 14-5/8" (144mm x 365mm x 373mm) (When the Auxiliary Tray is extended)
Weight:	Approximately 1 lb. (438g)

Inner 2-Way Tray-F1□□□

Number of Trays:	2
Total Output Capacity:	Top Tray: 100 Sheets (20 lb. Bond) Lower Tray: 250 Sheets (20 lb. Bond)
Acceptable Paper Weight:	17 lb. Bond to 80 lb. Cover (64 to 220g/m ²)
Acceptable Paper Size:	12" x 18", 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18" [99mm x 139.7mm to 320mm x 457.2mm]) and Envelopes
Dimensions (H x W x D):	3" x 16-3/4" x 16" (76mm x 426mm x 407mm)
Weight:	Approximately 1.3 lb. (574g)

Inner Finisher-C1

Number of Trays:	Up to 2 Trays (With Inner Finisher Additional Tray-A1)
Total Output Capacity:	Without Inner Finisher Additional Tray-A1 750 Sheets With Inner Finisher Additional Tray-A1 Top Tray: 100 Sheets (Letter) Lower Tray: 350 Sheets (Letter)
Acceptable Paper Weight:	17 lb. Bond to 80 lb. Cover (64 to 220g/m ²)
Acceptable Paper Size:	12" x 18", 11" x 7", Legal, Letter, Letter-R, Statement, Statement-R, Executive, Custom Size (3-7/8" x 5-1/2" to 12-5/8" x 18" [99mm x 139.7mm to 320mm x 457.2mm]) and Envelopes
Staple Positions:	Corner Stapling: (11" x 17", Legal, Letter, Letter-R) Double Stapling: (11" x 17", Legal, Letter, Letter-R) Letter: 50 Sheets (17 lb. Bond - 21 lb. Bond) 30 Sheets (22 lb. Bond - 28 lb. Bond) 2 Sheets (29 lb. Bond - 80 lb. Cover) 11"x17", Legal, Letter-R: 30 Sheets (17 lb. Bond - 21 lb. Bond) 20 Sheets (22 lb. Bond - 28 lb. Bond) 2 Sheets (29 lb. Bond - 80 lb. Cover)
Maximum Stapling Capacity:	Top Tray: 15 Sets (or 3/8" in height) Lower Tray: 30 Sets (or 3-3/4" in height)
Paper Capacity of Staple Mode:	Staple-J1 (5,000 x 3)
Type of Staple:	Staple-J1 (5,000 x 3)
Power Source/Maximum Power Consumption:	From the Main Unit/Approximately 48W
Dimensions (H x W x D):	10-1/4" x 27-1/2" x 21-1/4" (260mm x 700mm x 540mm) (When the Auxiliary Tray is extended)
Weight:	Approximately 31 lb. (14kg) (When Inner Finisher Additional Tray-A1 is attached)

Other Optional Accessories

- Cabinet Type-D*
- Inner Finisher Additional Tray-A1
- Utility Tray-A2
- USB Keyboard
- Copy Card Reader-C1♦♦
- Copy Card Reader Attachment-B2
- Braille Label Kit-F1
- ADF Access Handle-A1
- Copy Control Interface Kit-A1♦♦♦
- Stamp Ink Cartridge-C1
- Stamp Unit-B1
- imageRUNNER ADVANCE Essentials
- PS Printer Kit-AG1
- PCL Printer Kit-AG1
- Direct Print Kit (for PDF/XPS)-H1
- Encrypted Secure Print Software-D1
- Barcode Printing Kit-D1*
- Web Access Software-H1♦♦
- Universal Send Advanced Feature Set-E1
- Universal Send Security Feature Set-D1
- Universal Send Digital User Signature Kit-C1
- Super G3 FAX Board-AH1
- Super G3 2nd Line FAX Board-AH1♦♦♦
- Remote Fax Kit-A1[△]
- Secure Watermark-B1
- Wireless LAN Board-B2^{△△}
- USB Device Port-C1
- Multimedia Reader/Writer-A2[■]
- Document Scan Lock Kit-A3^{†††}
- Data Erase Kit-C1
- HDD Data Encryption Kit-C3
- Removable HDD Kit-AE1
- IPsec Board-B2^{△△}
- Expansion Bus-F2
- Voice Guidance Kit-F2[■]
- Voice Operation Kit-C2[■]
- Remote Operators Software Kit-B1
- eCopy Suite
- imageWARE Suite

* Can be set to Cassette 2 only.

□ Includes consumables.

□□ Installs on Cassette 2.

□□□ Cannot be installed with Inner Finisher-C1.

[†] If 1200 dpi is selected, engine speed will slow down.

^{††} EPS and XPS cannot be printed from Memory Media.

^{†††} Check with your Canon Authorized Dealer for availability.

♦ Cannot be installed when Cassette Feeding Unit-AF1 is installed.

♦♦ Requires Copy Card Reader Attachment Kit-B2.

♦♦♦ Cannot be installed with Copy Card Reader-C1.

△ Requires PCL Printer Kit-AG1.

♦♦ Requires PS Printer Kit-AG1 or Direct Printer Kit (for PDF/XPS)-H1 for printing PDF files.

♦♦♦ Requires Super G3 Fax Board-AH1.

△ Cannot be installed with Super G3 Fax Board-AH1.

△△ Requires Expansion Bus F2.

■ Requires Device Port-B1.

■ The Voice Operation Kit-F2 and Voice Operation Kit-C2 cannot be installed together.

Canon
*image*ANYWARE

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and hereby acknowledged. Some items may not be available at this time; please check for availability. Specifications and availability subject to change without notice.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.

©2013 Canon U.S.A., Inc. All rights reserved.

